

## SAFETY DATA SHEET

Date of issue: 14.04.2006

Date to update : 11.05.2009

Number: LB\_3\_04\_01\_A

Page: 1 of 4

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**1.1. Identification of the preparation: OPTIC ACRYL TOPCOAT 2+1 LA:** 002A ,005A, 105, 107A, 110, 118, 121,127 165, 202A, 203, 208, 210A, 215A, 225, 303, 320, 355, 394, 422, 425, 440 456, 530A, 564, 828, 1015, 1021, 1025, 1035

**OPTIC ACRYL TOPCOAT 2+1 RAL:** 1000, 1002, 1003, 1004, 1007,1013 1018, 1021, 1023, 1028, 1032, 2000, 2001, 2002, 2004, 2008, 2010,2011, 3000, 3002, 3004, 3020,5018, 6001, 6007, 6009, 6010, 6011, 6016, 6017, 6018, 6024, 6027, 6028, 6029,7001, 7011,7021PMAT, 7035, 9002, 9003, 9007, AFRICA YELLOW, AUTONADWOAZIA MERCEDES, S141, S412, S450, SA 066, S.A. 298, S.A. 300, S.A. 303 S.A. 507, S.A. 880, SB 175, SB 880, SD 240, SD 866,CZERWIEN' MEKSYKAŃSKA, ZIELONY AUTONADWOZIA, CZERWONY AUTONADWOZIA, OPTIC EA TOYOTA 56A1, LA RAMA DAF

**1.2. Use of the preparation:** Two-component acryl topcoat (component A) for application with a spray gun used in car refinsh.

**1.3. Company/undertaking identification:** **NOVOL** Sp. z o.o. Tel: +48 61 810-98-00  
ul. Żabikowska 7/9 Fax: +48 61 810-98-09  
62-052 Komorniki [www.novol.pl](http://www.novol.pl)  
Emergency tel: (061) 810-98-00

**2. HAZARD IDENTIFICATION**

**HEALTH HAZARDS:** Toxic product. Harmful by inhalation and in contact with skin. Danger of cumulative effects. Carc.cat.3 Limited evidence of a carcinogenic effect. Repr.Cat.1 May cause harm to the unborn child. Repr.Cat.2 May cause cancer. Repeated exposure may cause skin dryness or cracking.

**DANGEROUS PROPERTIES:** Flammable liquid; avoid contact with strong oxidants. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

**OTHER:** No data available.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

EEC No.	Name of the substance	WE No.	CAS No.	Classification of the substance	Marking of the substance	Composition
607-195-00-7	2-Methoxy-1-methylethyl acetate	203-603-9	108-65-6	R10 Xi; R36	Xi R: 10-36 S: (2-)25	5-10%
607-025-00-1	Butyl acetate	204-658-1	123-86-4	R10 R66-67	R: 10-66-67 S: (2-)25	15-20%
601-022-00-9	Xylene	215-535-7	1330-20-7	R10 Xn, R20/21 Xi, R38	Xn R: 10-20/21-38 S: (2-)25	10-15%
607-038-00-2	2-butoxyethyl acetate	203-933-3	112-07-2	Xn; R20/21	Xn R: 20/21 S: (2-)24	1-5%
	Ethyl 3-ethoxypropionate		763-69-9	R10	R10 S: 16-3/7	1-5%
082-009-00-X	lead sulfochromate yellow (C.I. 77603);	215-693-7	1344-37-2	Carc.Cat.2; R45 Repr. Cat.1; R61 Repr. Cat.3; R62 R33 N; R50-53	T; N R: 61-33-45-50/53-62 S: 53-45-60-61	<15%
082-010-00-5	lead chromate molybdate sulfate red (C.I. 77605);	235-759-9	12656-85-8	Carc.Cat.2; R45 Repr. Cat.1; R61 Repr. Cat.3; R62 R33 N; R50-53	T; N R: 61-33-45-50/53-62 S: 53-45-60-61	<9%

**4. FIRST AID MEASURES**

**GENERAL INFORMATION:** See 11 point Product Date Sheet.

**INHALATION:** Take the casualty into the fresh air and keep warm irregular breathing/no breathing artificial respiration call a physician.

**SKIN:** Take off soiled clothes. Wash off with plenty of lukewarm water (at least 15 minutes).Consult a doctor in the event of skin reaction.

**EYES:** Hold the eyes open and rinse immediately with plenty of lukewarm water (at least 15 minutes). Contact with ophthalmologist.

**ALIMENTARY TRACT:** Do not provoke vomiting (risk of choking). Rinse mouth with water. Medical help is required.

**SAFETY DATA SHEET**

**OPTIC ACRYL TOPCOAT 2+1 LA:** 002A ,005A, 105, 107A, 110, 118, 121,127 165, 202A, 203, 208, 210A, 215A, 225, 303, 320, 355, 394, 422, 425, 440 456, 530A ,564, 828, 1015, 1021, 1025, 1035

**OPTIC ACRYL TOPCOAT 2+1 RAL:** 1000, 1002, 1003, 1004, 1007,1013 1018, 1021, 1023, 1028, 1032, 2000, 2001, 2002, 2004, 2008, 2010,2011, 3000, 3002, 3004, 3020,5018, 6001, 6007, 6009, 6010, 6011, 6016, 6017, 6018, 6024, 6027, 6028, 6029,7001, 7011,7021PMAT, 7035, 9002, 9003, 9007, AFRICA YELLOW, AUTONADWOAZIA MERCEDES, S141, S412, S450, SA 066, S.A. 298, S.A. 300, S.A. 303 S.A. 507, S.A. 880, SB 175, SB 880, SD 240, SD 866,CZERWIEN MEKSYKAŃSKA, ZIELONY AUTONADWOZIA, CZERWONY AUTONADWOZIA, OPTIC EA TOYOTA 56A1, LA RAMA DAF

Date of issue: 14.04.2006

Date to update : 11.05.2009

Number: LB\_3\_04\_01\_A

Page: 2 of 4

**5. FIRE-FIGHTING MEASURES****FIRE EXTINGUISHING****SUBSTANCES:**

Powder, foam resistant to alcohols, carbon dioxide, watermist.

**SPECIAL HAZARDS:**

Fire may cause the generation of carbon monoxide.

**PROTECTIVE EQUIPMENT:**

Firemen have to wear self-contained breathing apparatus and protective clothing.

**OTHER INFORMATION:**

Cool adjacent tanks by spraying water from a safe distance.

**6. ACCIDENTAL RELEASE MEASURES****PERSONAL PROTECTION:**

Eliminate sources of ignition. Ensure sufficient ventilation in this room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Put on protective equipment see chapter 8.

**PROTECTION OF THE ENVIRONMENT:**

Prevent to get through to the sewage system, to the surface water, underground water, to the soil. In case of a major spillage the affected area should be separated with bounds.

**ACTION IN CASE OF SPILLAGE:**

Seal the container; damaged containers should be placed in emergency containers. Besprinkle spillage, use e.g. mica, sand, wood flour. Remove the substance mechanically and put to emergency containers. For further disposal measures: see chapter 13.

**7. HANDLING AND STORAGE****HANDLING RULES:**

Keep away from heat and sources of fire. Do not smoke. Do not inhale vapours. Avoid contact with skin and eyes. Take precautionary measures against electrostatic loading. Use only in well ventilated place. Put on protective equipment-see chapter 8.

**STORAGE:**

Keep in sealed containers in cool, well ventilated rooms. Storage in the vicinity of a large quantity of organic peroxides or strong oxidants is prohibited.

**PECULIAR APPLICATION:**

See the technical product data sheet..

**8. EXPOSURE CONTROLS/ PERSONAL PROTECTION**

**LIMIT VALUES:** for Xylene CAS 1330-20-7 according to:

- *TRGS 900:* MAK: 100ppm, MAK: 440 mg/m<sup>3</sup>, 2(II),DFG, H
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 mg/m<sup>3</sup>, 220mg/m<sup>3</sup>, STEL 100ppm, 441 mg/m<sup>3</sup>, Sk, BMGV for 2-methoxy-1-methylethyl acetate CAS 108-65-6 according to:
- *TRGS 900:* MAK: 50ppm, MAK: 270 mg/m<sup>3</sup>, 1(I),DFG, EU, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 ppm, 274 mg/m<sup>3</sup>, STEL 100ppm, 548 mg/m<sup>3</sup>, Sk for Butyl acetate CAS 123-86-4 according to:
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 150 ppm, 724 mg/m<sup>3</sup>, STEL 200ppm, 966 mg/m<sup>3</sup> for 2-butoxyethyl acetate CAS 112-07-2 according to:
- *TRGS 900:* MAK: 20ppm, MAK:130 mg/m<sup>3</sup>, 4(II) DFG, H, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 20 ppm, STEL 50ppm, Sk

**RESPIRATORY TRACT PROTECTION:**

Gas mask with "A" type absorbing canister.

**PROTECTION OF HANDS:**

Protective gloves suitable for handling solvents (viton, nitrile rubber, vinyl polialcohol).

**EYES PROTECTION:**

Protective glasses.

**SKIN PROTECTION:**

Suitable protective clothing (antistatic, impregnated clothing).

**WORKPLACE:**

Topical stays and exhausting ventilation.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state:

liquid

Colour:

according to palette's colour

Smell:

pungent, penetrating odour

Boiling point:

126-190°C

Flash-point:

23°C

Autoignition point:

approx.300°C

Explosion limits:

% lower: 1.1 vol.% upper: 8.8 vol.% (butyl acetate)

Vapour pressure:

9.4 hPa (20°C)

Density:

approx. 1.12 g/cm<sup>3</sup> (20°C)

Water solubility:

insoluble

Viscosity (Ford φ4):

approx. 120 s

**SAFETY DATA SHEET**

**OPTIC ACRYL TOPCOAT 2+1 LA:** 002A ,005A, 105, 107A, 110, 118, 121,127 165, 202A, 203, 208, 210A, 215A, 225, 303, 320, 355, 394, 422, 425, 440 456, 530A ,564, 828, 1015, 1021, 1025, 1035

**OPTIC ACRYL TOPCOAT 2+1 RAL:** 1000, 1002, 1003, 1004, 1007,1013 1018, 1021, 1023, 1028, 1032, 2000, 2001, 2002, 2004, 2008, 2010,2011, 3000, 3002, 3004, 3020,5018, 6001, 6007, 6009, 6010, 6011, 6016, 6017, 6018, 6024, 6027, 6028, 6029,7001, 7011,7021PMAT, 7035, 9002, 9003, 9007, AFRICA YELLOW, AUTONADWOAZIA MERCEDES, S141, S412, S450, SA 066, S.A. 298, S.A. 300, S.A. 303 S.A. 507, S.A. 880, SB 175, SB 880, SD 240, SD 866,CZERWIEN MEKSYKAŃSKA, ZIELONY AUTONADWOZIA, CZERWONY AUTONADWOZIA, OPTIC EA TOYOTA 56A1, LA RAMA DAF

Date of issue: 14.04.2006

Date to update: 11.05.2009

Number: LB\_3\_04\_01\_A

Page: 3 of 4

**10. STABILITY AND REACTIVITY**

**STABILITY:** The product remains stable under normal conditions.

**AVOID THE CONTACT OF THE MATERIAL WITH:** Strong oxidants, high temperature, strong acids and basis.

**DANGEROUS DECOMPOSITION PRODUCTS:** Carbon monoxide and other toxic gasses are generated as a result of thermal decomposition.

**11. TOXICOLOGICAL INFORMATION**

Toxicological studies at the preparation are not available.

**TOXICITY:** Xylene LD<sub>50</sub> (rat, oral) 5000 mg/kg  
 LC<sub>50</sub> (rat, inhalation) 4550 ppm/4h  
 lead chromate molybdate sulfate red: LD<sub>50</sub> (rat, oral) 5000 mg/kg  
 lead sulfochromate yellow: LD<sub>50</sub> (rat, oral) 5000 mg/kg

**IRRITATING EFFECT:** Skin: irritating to skin and mucous membranes.  
 Eyes: irritating effect.

**SYMPTOMS OF POISONING:** Headache and vertigo, fatigue, decreased muscle power, sleepiness and, in exceptional instances, loss of consciousness. If swallowed, the substance may cause irritation of the alimentary tract, nausea, vomiting, and diarrhoea.

**12. ECOLOGICAL INFORMATION**

Ecological studies at the preparation are not available.

Product contains heavy metals lead and chrome. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment The product is very poorly soluble in water. Keep away from the sewage system, surface water, underground water, and soil.

lead chromate molybdate sulfate red Fish LC50>10000mg/l/96h  
 ead sulfochromate yellow: Fish LC50>10000mg/l/96h  
 Xylene: Daphnia magna/EC50 (48h.) > 7,4 mg/l  
 ID-Number: 206  
 Classification under Hazard to Water: 2

**13. DISPOSAL CONSIDERATIONS**

**RECOMMENDATION:** Product must be disposed of by special means in accordance with local regulations.

**REMAINS OF PRODUCT:** Remains of product in the tin should be carefully remove and harden using suitable hardener.  
**code of waste:** 08 01 11  
**ATTENTION:** Remains should be harden in small portions far from flammable substances. Much amount of heat is emitting in the time of reaction! Harden product is not harmfully substance and could be treat like plastics wastes (in accordance with the regulations).

**CLEAN TIN:** The tin is subject to cash deposit as guarantee and should be return to manufacturer.  
**code of waste:** 15 01 10

**TIN PARTLY EMPTY:** See remains of product.

**14. TRANSPORT INFORMATION**

**GENERAL INFORMATION:** Do not transport with materials class 1 (with the exception of materials class 1.4S) and with some of materials class 4.1 and 5.2. Avoid direct contact with materials class 5.1 and 5.2 in the time of transport. Do not use naked flame and do not smoke.

**ADR/RID:** UN 1263 PAINT, 3, III.

UN No.	Name of the raw material	Hazard identification number	Warning label required	Classification Code	Packaging group
1263	PAINT	30	3	F1	III

**IMDG- Code:** PAINT, CLASS 3, UN 1263, PG III.  
 EmS: F-E, S-E

**ICAO/IATA:** No data available.

**SAFETY DATA SHEET****OPTIC ACRYL TOPCOAT 2+1 LA:** 002A ,005A, 105, 107A, 110, 118, 121,127 165, 202A, 203, 208, 210A, 215A, 225, 303, 320, 355, 394, 422, 425, 440 456, 530A ,564, 828, 1015, 1021, 1025, 1035**OPTIC ACRYL TOPCOAT 2+1 RAL:** 1000, 1002, 1003, 1004, 1007,1013 1018, 1021, 1023, 1028, 1032, 2000, 2001, 2002, 2004, 2008, 2010,2011, 3000, 3002, 3004, 3020,5018, 6001, 6007, 6009, 6010, 6011, 6016, 6017, 6018, 6024, 6027, 6028, 6029,7001, 7011,7021PMAT, 7035, 9002, 9003, 9007, AFRICA YELLOW, AUTONADWOAZIA MERCEDES, S141, S412, S450, SA 066, S.A. 298, S.A. 300, S.A. 303 S.A. 507, S.A. 880, SB 175, SB 880, SD 240, SD 866,CZERWIEN MEKSYKAŃSKA, ZIELONY AUTONADWOZIA, CZERWONY AUTONADWOZIA, OPTIC EA TOYOTA 56A1, LA RAMA DAF

Date of issue: 14.04.2006

Date to update : 11.05.2009

Number: LB\_3\_04\_01\_A

Page: 4 of 4

**15. REGULATORY INFORMATION**

Safety data sheet in accordance with Directives:

67/548/EWG(2006/121/WE)

91/155/EWG (2001/58/WE)

1999/45/EC (2006/8/WE)

2006/1907/WE REACH

2008/1272/WE

Other regulations: ADR (2007-2009) , IMDG Code 2006 Edition

**CONTAINS:**

Xylene lead chromate molybdate sulfate red (C.I. 77605), lead sulfochromate yellow (C.I. 77603);

**HAZARD SYMBOL(S)**

T Toxic  
N Product dangerous for the environment  
Contains lead. Should not be used on surfaces liable to be chewed or sucked by children. Product for professional use only.

**RISK-PHRASES:**

R10 Flammable  
R20/21 Harmful by inhalation and in contact with skin  
R33 Danger of cumulative effects  
R45 May cause cancer  
R61 May cause harm to the unborn child  
R62 Possible risk of impaired fertility  
R66 Repeated exposure may cause skin dryness or cracking.  
R51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

**SAFETY-PHRASES:**

S ½ Keep locked up and out of the reach of children  
S 23 Do not breathe spray.  
S 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.  
S 38 In case of insufficient ventilation, wear suitable respiratory equipment.  
S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)  
S 53 Avoid exposure - obtain special instructions before use.  
S 61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

**16. OTHER INFORMATION**

Full text of the R from section 2 and 3:

R10 Flammable

R20/21 Harmful by inhalation and in contact with skin

R33 Danger of cumulative effects

R36 Irritating to eyes

R38 Irritating to skin

R45 May cause cancer

R61 May cause harm to the unborn child

R62 Possible risk of impaired fertility

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness.

R50/53 Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

R51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

Information contained herein is based on our current knowledge. This document does not constitute a warranty for product characteristics.

Issued by: NOVOL Sp. z o.o.

Information: Laboratory Research and Development; tel. +48 61 810 99 09