

SAFETY DATA SHEET

Date of issue: 14.04.2006

Date to update : : 30.01.2009

Number: LB_3_04_02_B

Page: 1 of 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- 1.1. Identification of the preparation:** **OPTIC ACRYL TOPCOAT 2+1 LA¹**
OPTIC ACRYL TOPCOAT 2+1 RAL²
- 1.2. Use of the preparation:** Two-component acryl topcoat (component A) for application with a spray gun used in car refinsh.
- 1.3. Company/undertaking identification:** **NOVOL** Sp. z o.o. Tel: +48 61 810-98-00
ul. Żabikowska 7/9 Fax: +48 61 810-98-09
62-052 Komorniki www.novol.pl
Emergency tel: (061) 810-98-00

2. HAZARD IDENTIFICATION**HEALTH HAZARDS:** Harmful product. Harmful by inhalation and in contact with skin.. Repeated exposure may cause skin dryness or cracking**DANGEROUS PROPERTIES:** Flammable liquid; avoid contact with strong oxidants.**OTHER:** No data available.**3. COMPOSITION / INFORMATION ON INGREDIENTS**

EEC No.	Name of the substance	WE No.	CAS No.	Classification of the substance	Marking of the substance	Composition
607-195-00-7	2-Methoxy-1-methylethyl acetate	203-603-9	108-65-6	R10 Xi; R36	Xi R: 10-36 S: (2-)25	7-10%
607-025-00-1	Butyl acetate	204-658-1	123-86-4	R10 R66-67	R: 10-66-67 S: (2-)25	16-20%
601-022-00-9	Xylene	215-535-7	1330-20-7	R10 Xn, R20/21 Xi, R38	Xn R: 10-20/21-38 S: (2-)25	9-12%
607-038-00-2	2-butoxyethyl acetate	203-933-3	112-07-2	Xn; R20/21	Xn R: 20/21 S: (2-)24	1-5%
	Ethyl 3-ethoxypropionate		763-69-9	R10	R10 S: 16-3/7	3-6%

4. FIRST AID MEASURES**GENERAL INFORMATION:** See 11 point Product Date Sheet.**INHALATION:** Take the casualty into the fresh air and keep warm irregular breathing/no breathing artificial respiration call a physician.**SKIN:** Take off soiled clothes. Wash off with plenty of lukewarm water (at least 15 minutes).Consult a doctor in the event of skin reaction.**EYES:** Hold the eyes open and rinse immediately with plenty of lukewarm water (at least 15 minutes). Contact with ophthalmologist.**ALIMENTARY TRACT:** Do not provoke vomiting (risk of choking). Rinse mouth with water. Medical help is required.**5. FIRE-FIGHTING MEASURES****FIRE EXTINGUISHING****SUBSTANCES:** Powder, foam resistant to alcohols, carbon dioxide, watermist.**SPECIAL HAZARDS:** Fire may cause the generation of carbon monoxide.**PROTECTIVE EQUIPMENT:** Firemen have to wear self-contained breathing apparatus and protective clothing.**OTHER INFORMATION:** Cool adjacent tanks by spraying water from a safe distance.**6. ACCIDENTAL RELEASE MEASURES****PERSONAL PROTECTION:** Eliminate sources of ignition. Ensure sufficient ventilation in this room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Put on protective equipment see chapter 8.**PROTECTION OF THE ENVIRONMENT:** Prevent to get through to the sewage system, to the surface water, underground water, to the soil. In case of a major spillage the affected area should be separated with bounds.**ACTION IN CASE OF SPILLAGE:** Seal the container; damaged containers should be placed in emergency containers. Besprinkle spillage, use e.g. mica, sand, wood flour. Remove the substance mechanically and put to emergency containers. For further disposal measures: see chapter 13.

SAFETY DATA SHEET
OPTIC ACRYL TOPCOAT 2+1 LA¹
OPTIC ACRYL TOPCOAT 2+1 RAL²

Date of issue: 14.04.2006

Date to update : 30.01.2009

Number: LB_3_04_02_B

Page: 2 of 4

7. HANDLING AND STORAGE

HANDLING RULES:

Keep away from heat and sources of fire. Do not smoke. Do not inhale vapours. Avoid contact with skin and eyes. Take precautionary measures against electrostatic loading. Use only in well ventilated place. Put on protective equipment-see chapter 8.

STORAGE:

Keep in sealed containers in cool, well ventilated rooms. Storage in the vicinity of a large quantity of organic peroxides or strong oxidants is prohibited.

PECULIAR APPLICATION: See the technical product data sheet..

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

LIMIT VALUES:

for Xylene CAS 1330-20-7 according to:

- *TRGS 900:* MAK: 100ppm, MAK: 440 mg/m³, 2(II),DFG, H
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 mg/m³, 220mg/m³, STEL 100ppm, 441 mg/m³, Sk, BMGV

for 2-methoxy-1-methylethyl acetate CAS 108-65-6 according to:

- *TRGS 900:* MAK: 50ppm, MAK: 270 mg/m³, 1(I),DFG, EU, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 ppm, 274 mg/m³, STEL 100ppm, 548 mg/m³, Sk

for Butyl acetate CAS 123-86-4 according to:

- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 150 ppm, 724 mg/m³, STEL 200ppm, 966 mg/m³

for 2-butoxyethyl acetate CAS 112-07-2 according to:

- *TRGS 900:* MAK: 20ppm, MAK:130 mg/m³, 4(II) DFG, H, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 20 ppm, STEL 50ppm, Sk

RESPIRATORY TRACT PROTECTION:

Gas mask with "A" type absorbing canister.

PROTECTION OF HANDS:

Protective gloves suitable for handling solvents (viton, nitrile rubber, vinyl polialcohol).

EYES PROTECTION:

Protective glasses.

SKIN PROTECTION:

Suitable protective clothing (antistatic, impregnated clothing).

WORKPLACE:

Topical stays and exhausting ventilation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	liquid
Colour:	according to palette's colour
Smell:	pungent, penetrating odour
pH:	--
Boiling point:	127°C
Flash-point:	23°C
Autoignition point:	approx.300°C
Explosion limits:	% lower: 1.0 vol.% upper: 8.0 vol.% (butyl acetate) % dolna: 1.07 vol% góna: 10.55 vol% (Xylene)
Vapour pressure:	no dates
Density:	approx. 1.0 – 1.26 g/cm ³ (20°C) depending on colour
Water solubility:	insoluble
Partition coefficient n-octanol/water:	--
Viscosity (Ford φ4):	110-130 s

10. STABILITY AND REACTIVITY

STABILITY:

The product remains stable under normal conditions.

AVOID THE CONTACT OF THE MATERIAL WITH:

Strong oxidants, high temperature, strong acids and basis.

DANGEROUS DECOMPOSITION PRODUCTS:

Carbon monoxide and other toxic gasses are generated as a result of thermal decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicological studies at the preparation are not available.

TOXICITY: Xylene

LD₅₀ (rat, oral)

5000 mg/kg

LC₅₀ (rat, inhalation)

4550 ppm/4h

IRRITATING EFFECT:

Skin: irritating to skin and mucous membranes.

Eyes: irritating effect.

SYMPTOMS OF POISONING:

Headache and vertigo, fatigue, decreased muscle power, sleepiness and, in exceptional instances, loss of consciousness. If swallowed, the substance may cause irritation of the alimentary tract, nausea, vomiting, and diarrhoea.

SAFETY DATA SHEET
OPTIC ACRYL TOPCOAT 2+1 LA¹
OPTIC ACRYL TOPCOAT 2+1 RAL²

Date of issue: 14.04.2006

Date to update: 30.01.2009

Number: LB_3_04_02_B

Page: 3 of 4

12. ECOLOGICAL INFORMATION

Ecological studies at the preparation are not available.

2-Methoxy-1-methylethyl acetate: Daphnia magna/EC50 (48h.) > 500 mg/l
 Oncorhynchus mykiss/LC50 (96h.) 100-180 mg/l
 Number in catalogue includes substance danger to water : 5033
 Water hazard class : 1

Xylene: Daphnia magna/EC50 (48h.) > 7,4 mg/l
 ID-Number: 206
 Classification under Hazard to Water: 2

Butyl acetate: ID-Number: 42
 Classification under Hazard to Water: 1

The product is very poorly soluble in water. Keep away from the sewage system, surface water, underground water, and soil.

13. DISPOSAL CONSIDERATIONS

RECOMMENDATION: Product must be disposed of by special means in accordance with local regulations.

REMAINS OF PRODUCT: Remains of product in the tin should be carefully remove and harden using suitable hardener.
code of waste: 08 01 11

ATTENTION: Remains should be harden in small portions far from flammable substances. Much amount of heat is emitting in the time of reaction! Harden product is not harmfully substance and could be treat like plastics wastes (in accordance with the regulations).

CLEAN TIN: Tin carefully clean is not harmful waste.
code of waste: 15 01 04

TIN PARTLY EMPTY: See remains of product.

14. TRANSPORT INFORMATION

GENERAL INFORMATION: Do not transport with materials class 1 (with the exception of materials class 1.4S) and with some of materials class 4.1 and 5.2. Avoid direct contact with materials class 5.1 and 5.2 in the time of transport. Do not use naked flame and do not smoke.

ADR/RID: UN 1263 PAINT, 3, III.

UN No.	Name of the raw material	Hazard identification number	Warning label required	Classification Code	Packaging group
1263	PAINT	30	3	F1	III

IMDG- Code: PAINT, CLASS 3, UN 1263, PG III.
 EmS: F-E, S-E

ICAO/IATA: No data available.

15. REGULATORY INFORMATION

Safety data sheet in accordance with Directives:

67/548/EWG(2006/121/WE)

91/155/EWG (2001/58/WE)

1999/45/EC (2006/8/WE)

2006/1907/WE REACH

1272/2008/WE

Other regulations: ADR (2007-2009) , IMDG Code 2006 Edition

CONTAINS: Xylene



HAZARD SYMBOL(S) Xn Harmful

RISK-PHRASES: R10 Flammable.
 R20/21 Harmful by inhalation and in contact with skin.
 R 66 Repeated exposure may cause skin dryness or cracking.

SAFETY-PHRASES: S (2-) Keep out of the reach of children.
 S 23 Do not breathe vapour/spray.
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
 S 38 In case of insufficient ventilation, wear suitable respiratory equipment
 S 46 If swallowed, seek medical advice immediately and show this container or label.

SAFETY DATA SHEET

OPTIC ACRYL TOPCOAT 2+1 LA¹

OPTIC ACRYL TOPCOAT 2+1 RAL²

Date of issue: 14.04.2006

Date to update: 30.01.2009

Number: LB_3_04_02_B

Page: 4 of 4

16. OTHER INFORMATION

Full text of the R from section 2 and 3:

R10 Flammable

R20/21 Harmful by inhalation and in contact with skin

R36 Irritating to eyes;

R38 Irritating to skin.

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness.

Information contained herein is based on our current knowledge. This document does not constitute a warranty for product characteristics.

Issued by: NOVOL Sp. z o.o.

Information: Laboratory Research and Development; tel. +48 61 810 99 09

¹ OPTIC ACRYL TOPCOAT 2+1 LA :

001
001A
002A
003A
003
004A
006A
101
106
107
127
170
180
180A
181
181A
182
182A
201
202
202A
203
210
210A
215
228
233
233A
235
235A
236
236A
236AZ
295
307
307A
309
320
325
355
360
377
400
403
404
404A
410
417
420
422
425
425A
427
427A
428
440
440A
447
447A
449
449A
458
464
464A
480
481
506
509
509A
601
601A
605
610
671

671A
793
1021
1027
ML 1110
1115

aktualizacja: 30-01-2009

² **OPTIC ACRYL TOPCOAT 2+1 RAL:**

1001
1011
1013
1015
1016
1037
3001
3003
3005
3011
3027
4001
4003
4004
4006
4008
4010
5002
5004
5005
5010
5012
5013
5015
5017
5019
5021
5022
6003
6003 półmat
6005
6011
6012
6020
6033
6033 półmat
6034
7011
7011 półmat
7011 mat
7016
7021
7021 półmat
7024
7024 półmat
7026
7031
7037
7038 półmat
7040
7043
7047
9001
9003
9004
9005
9005 mat
9005 półmat
9006
9010
9011
9016
9018

INNE:

S 000

S 001

S 002

S 090

S 091

S 100

S 140

S 160

S 410

S 411

S 413

S 451

S 500

S 540

S 600

S 610

S 700

S 710

S 800

SA 122

SA 134

SA 303

SA 360

SA 454

SA 514

SA 773

SA 935

SA 940

SA 958

SA 959

SA 990

SA 999

NIEBIESKI AUTONADWOZIA

YASMA

LA YASMA A

LA RENAULT A70

LA AFRICA DARK RED

LA AFRICA PINK

LA AFRICA RED

LA RENO A

LA SK IVECO

LA SK RENAULT

LA RAMA SCANIA

RAL TOYOTA 040

aktualizacja: 30-01-2009