

SAFETY DATA SHEET

Date of issue: 09.07.2007

Date to update : 09.10.2007

Number: SB_8_21

Page: 1 of 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**1.1. Identification of the preparation:** ACRYL CLEARCOAT, SPECTRAL KLAR 515 (VHS)**1.2. Use of the preparation:** Two-component clearcoat (component A) for application with a spray gun.**1.3. Company/undertaking identification:** NOVOL Sp. z o.o. Tel: +48 61 810-98-00
ul. Żabikowska 7/9 Fax: +48 61 810-98-09
62-052 Komorniki www.novol.pl
Emergency tel: (061) 810-98-00**2. HAZARD IDENTIFICATION****HEALTH HAZARDS:** Harmful product. Harmful by inhalation. Repeated exposure may cause skin dryness or cracking.**DANGEROUS PROPERTIES:** Flammable liquid; avoid contact with strong oxidants. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.**OTHER:** No data available.**3. COMPOSITION / INFORMATION ON INGREDIENTS**

EEC No.	Name of the substance	WE No.	CAS No.	Classification of the substance	Marking of the substance	Composition
607-025-00-1	Butyl acetate	204-658-1	123-86-4	R10 R66-67	R: 10-66-67 S: (2-)25	20-30%
601-022-00-9	Xylene	215-535-7	1330-20-7	R10 Xn, R20/21 Xi, R38	Xn R: 10-20/21-38 S: (2-)25	1-5%
606-024-00-3	Methyl amyl ketone	203-767-1	110-43-0	R10 Xn; R20/22	Xn R: 10-20/22 S: (2-)24/25	10-15%
649-356-00-4	Solvent naphtha (petroleum), light arom.	265-199-0	64742-95-6	Rakotw. Kat. 2; R45 Xn; R65	NOTA H, NOTA P NOTA 4 Xn, N R: 10-36/37/38-51/53-65-66-67 S:23-24-43a-57-60-62	2-3%
601-043-00-3	1,2,4-trimethylbenzene	202-436-9	95-63-6	R10 Xn; R20 Xi; R36/37/38 N; R51-53	Xn; N R: 10-20-36/37/38-51/53 S: (2-)26-61	1-5%
607-176-00-3	A mixture of: α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	400-830-7	104810-48-2+ 104810-47-1+ 25322-68-3	R43 N, R51-53	Xi, N R: 43-R51/53 S:(2-)36/37-61	0.5-0.8%

4. FIRST AID MEASURES**GENERAL INFORMATION:** See 11 point Product Data Sheet.**INHALATION:** Take the casualty into the fresh air and keep warm irregular breathing/no breathing artificial respiration call a physician.**SKIN:** Take off soiled clothes. Wash off with plenty of lukewarm water (at least 15 minutes). Consult a doctor in the event of skin reaction.**EYES:** Hold the eyes open and rinse immediately with plenty of lukewarm water (at least 15 minutes). Contact with ophthalmologist.**ALIMENTARY TRACT:** Do not provoke vomiting (risk of choking). Rinse mouth with water. Medical help is required.

SAFETY DATA SHEET**ACRYL CLEARCOAT, SPECTRAL KLAR 515 (VHS)**

Date of issue: 09.07.2007

Date of update : 09.10.2007

Number: SB_8_21

Page: 2 of 4

5. FIRE-FIGHTING MEASURES**FIRE EXTINGUISHING****SUBSTANCES:** Powder, foam resistant to alcohols, carbon dioxide, watermist.**SPECIAL HAZARDS:** Fire may cause the generation of carbon monoxide.**PROTECTIVE EQUIPMENT:** Firemen have to wear self-contained breathing apparatus and protective clothing.**OTHER INFORMATION:** Cool adjacent tanks by spraying water from a safe distance.**6. ACCIDENTAL RELEASE MEASURES****PERSONAL PROTECTION:** Eliminate sources of ignition. Ensure sufficient ventilation in this room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Put on protective equipment see chapter 8.**PROTECTION OF THE ENVIRONMENT:** Prevent to get through to the sewage system, to the surface water, underground water, to the soil. In case of a major spillage the affected area should be separated with bounds.**ACTION IN CASE OF SPILLAGE:** Seal the container; damaged containers should be placed in emergency containers. Besprinkle spillage, use e.g. mica, sand, wood flour. Remove the substance mechanically and put to emergency containers. For further disposal measures: see chapter 13.**7. HANDLING AND STORAGE****HANDLING RULES:**

Keep away from heat and sources of fire. Do not smoke. Do not inhale vapours. Avoid contact with skin and eyes. Take precautionary measures against electrostatic loading. Use only in well ventilated place. Put on protective equipment-see chapter 8.

STORAGE:

Keep in sealed containers in cool, well ventilated rooms. Storage in the vicinity of a large quantity of organic peroxides or strong oxidants is prohibited.

PECULIAR APPLICATION: See the technical product data sheet..**8. EXPOSURE CONTROLS/ PERSONAL PROTECTION****LIMIT VALUES:**

for Xylene CAS 1330-20-7 according to:

- *TRGS 900:* MAK: 100ppm, MAK: 440 mg/m³, 2(II),DFG, H
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 mg/m³, 220mg/m³, STEL 100ppm, 441 mg/m³, Sk, BMGV

for Methyl amyl ketone CAS 110-43-0 according to:

- *TRGS 900:* MAK: 238 mg/m³, 2(I),DFG
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 mg/m³, 237mg/m³, STEL 100ppm, 475 mg/m³, Sk

for Butyl acetate CAS 123-86-4 according to:

- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 150 ppm, 724 mg/m³, STEL 200ppm, 966 mg/m³

for 1,2,4-trimethylbenzene CAS 95-63-6 according to:

- *TRGS 900:* MAK: 20ppm, MAK: 100 mg/m³, 2(II),DFG, EU, Y

RESPIRATORY TRACT PROTECTION: Gas mask with "A" type absorbing canister.**PROTECTION OF HANDS:** Protective gloves suitable for handling solvents (viton, nitrile rubber).**EYES PROTECTION:** Protective glasses.**SKIN PROTECTION:** Suitable protective clothing (antistatic, impregnated clothing).**WORKPLACE:** Topical stays and exhausting ventilation.**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state: liquid
 Colour: colourless
 Smell: pungent, penetrating odour
 pH: --
 Boiling point: 126-140°C
 Flash-point: 23°C
 Autoignition point: 370°C
 Explosion limits: % lower: 1.0 vol.% upper: 8.0 vol.%
 Vapour pressure: 10.0 hPa (20°C)
 Density: approx. 1.0 g/cm³ (20°C)
 Water solubility: poorly soluble
 Partition coefficient n-octanol/water: --
 Viscosity (Ford φ4): approx 21s

SAFETY DATA SHEET**ACRYL CLEARCOAT, SPECTRAL KLAR 515 (VHS)**

Date of issue: 09.07.2007

Date to update : 09.10.2007

Number: SB_8_21

Page: 3 of 4

10. STABILITY AND REACTIVITY**STABILITY:** The product remains stable under normal conditions.**AVOID THE CONTACT OF THE MATERIAL WITH:** Strong oxidants, high temperature, strong acids and basis.**DANGEROUS DECOMPOSITION PRODUCTS:** Carbon monoxide and other toxic gasses are generated as a result of thermal decomposition.**11. TOXICOLOGICAL INFORMATION**

Toxicological studies at the preparation are not available.

TOXICITY: Methyl amyl ketone LD₅₀ (rat, oral) 1,600 mg/kg
LC₅₀ (rat, inhalation) 2000-4000 ppm/4hButyl acetate LD₅₀ (rat, oral) 1400 mg/kg
LC₅₀ (rat, inhalation) 9660 mg/m³/8h**IRRITATING EFFECT:** Skin: irritating to skin and mucous membranes.
Eyes: irritating effect.**SYMPTOMS OF POISONING:** Headache and vertigo, fatigue, decreased muscle power, sleepiness and, in exceptional instances, loss of consciousness. If swallowed, the substance may cause irritation of the alimentary tract, nausea, vomiting, and diarrhoea.**12. ECOLOGICAL INFORMATION**

Ecological studies at the preparation are not available.

Xylene: Daphnia magna/EC50 (48h.) > 7,4 mg/l
ID-Number: 206Butyl acetate: ID-Number: 42
Classification under Hazard to Water: 1

The product is very poorly soluble in water. Keep away from the sewage system, surface water, underground water, and soil.

13. DISPOSAL CONSIDERATIONS**RECOMMENDATION:** Product must be disposed of by special means in accordance with local regulations.**REMAINS OF PRODUCT:** Remains of product in the tin should be carefully remove and harden using suitable hardener. Harden product is not harmfully substance and could be treat like plastics wastes (in accordance with the regulations).
code of waste: 08 01 11**ATTENTION:** Remains should be harden in small portions far from flammable substances. Much amount of heat is emitting in the time of reaction!**CLEAN TIN:** Tin carefully clean is not harmful waste.**code of waste:** 15 01 04**TIN PARTLY EMPTY:** See remains of product.**14. TRANSPORT INFORMATION****GENERAL INFORMATION:** Do not transport with materials class 1 (with the exception of materials class 1.4S) and with some of materials class 4.1 and 5.2. Avoid direct contact with materials class 5.1 and 5.2 in the time of transport. Do not use naked flame and do not smoke.**ADR/RID:** UN 1866 RESIN SOLUTIONS, FLAMMABLE, 3, III.

UN No.	Name of the raw material	Hazard identification number	Warning label required	Classification Code	Packaging group
1866	RESIN SOLUTIONS, FLAMMABLE	30	3	F1	III

IMDG- Code: RESIN SOLUTIONS, FLAMMABLE, CLASS 3, UN 1866, PG III.
EmS: F-E, S-E**ICAO/IATA:** No data available.**15. REGULATORY INFORMATION**

Safety data sheet in accordance with Directives:

67/548/EWG(2006/121/WE)

91/155/EWG (2001/58/WE)

1999/45/EC (2006/8/WE)

2006/1907/WE REACH

Other regulations: ADR (2007-2009) , IMDG Code 2006 Edition

SAFETY DATA SHEET**ACRYL CLEARCOAT, SPECTRAL KLAR 515 (VHS)**

Date of issue: 09.07.2007

Date to update : 09.10.2007

Number: SB_8_21

Page: 4 of 4

15. REGULATORY INFORMATION**CONTAINS:** Butyl acetale, Methyl amyl ketone**HAZARD SYMBOL(S)** Xn Harmful**RISK-PHRASES:**
R10 Flammable.
R20 Harmful by inhalation.
R66 Repeated exposure may cause skin dryness or cracking.
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.**SAFETY-PHRASES:**
S (2-) Keep out of the reach of children.
S 23 Do not breathe vapour/spray.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S 38 In case of insufficient ventilation, wear suitable respiratory equipment
S 46 If swallowed, seek medical advice immediately and show this container or label.**16. OTHER INFORMATION**

Full text of the R -Phrases from sections 2 and 3:

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R20/22 Harmful by inhalation and if swallowed

R36/37/38 Irritating to eyes, respiratory system and skin.

R38 Irritating to skin.

R45 May cause cancer.

R51 Toxic to aquatic organisms

R53 May cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Information contained herein is based on our current knowledge. This document does not constitute a warranty for product characteristics.

Issued by: NOVOL Sp. z o.o.

Information: Laboratory Research and Development; tel. +48 61 810 99 09