

SAFETY DATA SHEET

Date of issue: 20.07.2006

Date to update: 09.10.2007

Number: SB_8_24_02

Page: 1 of 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Identification of the preparation: **SPECTRAL BASE COAT METALLIC:** SB-810 FINE ALUMINIUM, SB-840 FINE SPECIAL ALUMINIUM, SB-820 MEDIUM FINE ALUMINIUM, SB-830 MEDIUM COARSE ALUMINIUM, SB-850 MEDIUM ALUMINIUM, SB-860 BRIGHT COARSE ALUMINIUM, SB-870 EXTRA COARSE ALUMINIUM, SB-880 COARSE ALUMINIUM

1.2. Use of the preparation: Metallic base coat contain obtained through mixing pigment pastes with binder, according to NOVOL formulas. The product is designated for use in the coating systems of new motor vehicles, new goods transport vehicles

1.3. Company/undertaking identification: **NOVOL Sp. z o.o.** Tel: (061) 810-98-00
ul. Zabikowska 7/9 Fax: (061) 810-98-09
62-052 Komorniki www.novol.pl
Emergency tel: (061) 810-98-00

2. HAZARD IDENTIFICATION

HEALTH HAZARDS: Harmful product. Harmful by inhalation and in contact with skin. Repeated exposure may cause skin dryness or cracking.

DANGEROUS PROPERTIES: Flammable liquid; that catch fire at temperatures in excess of 21°C if exposed to an ignition source. Avoid contact with strong oxidants. May cause long term adverse effects in the aquatic environment

OTHER: No data available.

3. COMPOSITION / INFORMATION ON INGREDIENTS

EEC No.	Name of the substance	WE No.	CAS No.	Classification of the substance	Marking of the substance	Composition
607-025-00-1	Butyl acetate	204-658-1	123-86-4	R10 R66-67	R: 10-66-67 S: (2-)25	40-50%
601-022-00-9	Xylene	215-535-7	1330-20-7	R10 Xn, R20/21 Xi, R38	Xn R: 10-20/21-38 S: (2-)25	10-15%
607-130-00-2	Pentyl acetate	211-047-3	628-63-7	R10; R66	R: 10-66 S: (2-)23-24	5-10%
603-004-00-6	Butan-1-ol	200-751-6	71-36-3	R10 Xn; R22 Xi; R37/38-41 R67	Xn R: 10-22-37/38-41-67 S: (2-)7/9-13-26-37/39-46	1-3%
649-356-00-4	Solvent naphtha (petroleum), light arom.*	265-199-0	64742-95-6	Carc.Cat.2 R45 Xn; R65	Xn, N R: 10-37-51/53-65-66-67 S:23-24-43a-57-60-62	<3%
649-327-00-6	Naphtha (petroleum), hydrotreated heavy	265-150-3	64742-48-9	Carc.cat.2 R45 Xn; R65	NOTA H, NOTA P NOTA 4 Xn R: 10-65-66	<3%

*applied notes H, P and 4; contains weight benzene (no WE 200-753-7) below 0.1% Classification of the substance: no carcinogen

4. FIRST AID MEASURES

GENERAL INFORMATION: See 11 point Product Data Sheet.

INHALATION: Take the casualty into the fresh air and keep warm irregular breathing/no breathing artificial respiration call a physician.

SKIN: Take off soiled clothes. Wash off with plenty of lukewarm water with soap (at least 15 minutes).consult a doctor in the event of skin reaction.

EYES: Hold the eyes open and rinse immediately with plenty of lukewarm water (at least 15 minutes). Contact with ophthalmologist.

ALIMENTARY TRACT: Do not provoke vomiting. SEEK A MEDICAL EXAMINATION IMMEDIATELY and present Safety data sheet. Administer petrolatum; administer neither milk nor animal or vegetable fats of any kind.

SPECTRAL BASE COAT METALLIC: SB-810 FINE ALUMINIUM, SB-840 FINE SPECIAL ALUMINIUM, SB-820 MEDIUM FINE ALUMINIUM, SB-830 MEDIUM COARSE ALUMINIUM, SB-850 MEDIUM ALUMINIUM, SB-860 BRIGHT COARSE ALUMINIUM, SB-870 EXTRA COARSE ALUMINIUM, SB-880 COARSE ALUMINIUM

Date of issue: 20.07.2006

Date to update: 09.10.2007

Number: SB_8_24_02

Page: 2 of 4

5. FIRE-FIGHTING MEASURES

FIRE EXTINGUISHING

SUBSTANCES: Powder, foam, sand, CO₂.

SPECIAL HAZARDS: Fire may cause the generation of carbon monoxide.

PROTECTIVE EQUIPMENT: Firemen have to wear self-contained breathing apparatus and protective clothing.

OTHER INFORMATION: Cool adjacent tanks by spraying water from a safe distance.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION: Eliminate sources of ignition. Ensure sufficient ventilation in this room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Put on protective equipment see chapter 8.

PROTECTION OF THE ENVIRONMENT: Prevent to get through to the sewage system, to the surface water, underground water, to the soil. In case of a major spillage the affected area should be separated with bounds.

ACTION IN CASE OF SPILLAGE: Seal the container; damaged containers should be placed in emergency containers. Besprinkle spillage, use e.g. mica, sand, wood flour. Remove the substance mechanically and put to emergency containers. For further disposal measures: see chapter 13.

7. HANDLING AND STORAGE

HANDLING RULES: Keep away from heat and sources of fire. Do not smoke. Do not inhale vapours. Avoid contact with skin and eyes. Take precautionary measures against electrostatic loading. Do not eat and drink during working with product. Avoid contact with source of fire, incandescent materials and direct sunshine. Use only in well ventilated place. Put on protective equipment see chapter 8.

STORAGE: Keep in sealed containers in cool, well ventilated rooms. Storage in the vicinity of a large quantity of organic peroxides or strong oxidants is prohibited.

PECULIAR APPLICATION: See the technical product data sheet.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

LIMIT VALUES:

for Xylene CAS 1330-20-7 according to:

- *TRGS 900:* MAK: 100ppm, MAK: 440 mg/m³, 2(II),DFG, H
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 mg/m³, 220mg/m³, STEL 100ppm, 441 mg/m³, Sk, BMGV

for Butyl acetate CAS 123-86-4 according to:

- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 150 ppm, 724 mg/m³, STEL 200ppm, 966 mg/m³

for Butan-1-ol CAS 71-36-3: according to:

- *TRGS 900:* MAK: 100ppm, MAK: 310 mg/m³, 1(I),DFG, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA - mg/m³, -mg/m³, STEL 60 ppm, 154 mg/m³, Sk, BMGV

RESPIRATORY TRACT PROTECTION: Gas mask with "A" type absorbing canister.

PROTECTION OF HANDS: Protective gloves (viton, nitrile rubber).

EYES PROTECTION: Protective glasses.

SKIN PROTECTION: Suitable protective clothing (antistatic, impregnated clothing).

WORKPLACE: Topical stays and exhausting ventilation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	liquid
Colour:	metallic
Smell:	characteristic
Boiling point:	126-140°C
Flash-point:	23°C
Autoignition point:	approx. 370°C
Explosion limits:	% lower: 1.0 vol% upper: 8.0 vol% (butyl acetate)
Vapour pressure:	13 hPa (20°C) (butyl acetate)
Density:	approx. 0.96-0.99 g/cm ³ (20°C)
Water solubility:	not soluble
Partition coefficient n-octanol/water:	--
Viscosity Ford φ4:	approx. 80 s

SPECTRAL BASE COAT METALLIC: SB-810 FINE ALUMINIUM, SB-840 FINE SPECIAL ALUMINIUM, SB-820 MEDIUM FINE ALUMINIUM, SB-830 MEDIUM COARSE ALUMINIUM, SB-850 MEDIUM ALUMINIUM, SB-860 BRIGHT COARSE ALUMINIUM, SB-870 EXTRA COARSE ALUMINIUM, SB-880 COARSE ALUMINIUM

Date of issue: 20.07.2006

Date to update: 09.10.2007

Number: SB_8_24_02

Page: 3 of 4

10. STABILITY AND REACTIVITY

STABILITY: The product remains stable under normal conditions.

AVOID THE CONTACT OF THE MATERIAL WITH: Strong oxidants, high temperature, strong acids and basis.

DANGEROUS DECOMPOSITION PRODUCTS: Carbon monoxide and other toxic gasses are generated as a result of thermal decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicological studies at the preparation are not available.

TOXICITY:

Xylene:	LD ₅₀ (rat, oral)	5000 mg/kg
	LC ₅₀ (rat, inhalation)	4550 ppm /4h

IRRITATING EFFECT: Skin: irritating to skin and mucous membranes.
Eyes: irritating effect.

SYMPTOMS OF POISONING: Headache and vertigo, fatigue, decreased muscle power, sleepiness and, in exceptional instances, loss of consciousness. If swallowed, the substance may cause irritation of the alimentary tract, nausea, vomiting, and diarrhoea.

12. ECOLOGICAL INFORMATION

Ecological studies at the preparation are not available.

Xylene: Daphnia magna/EC50 (48h.) > 7,4 mg/l
ID-Number: 206
Classification under Hazard to Water: 2

Butyl acetate: ID-Number: 42
Classification under Hazard to Water: 1

The product is very poorly soluble in water. Keep away from the sewage system, surface water, underground water, and soil. Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

RECOMMENDATION: Product must be disposed of by special means in accordance with local regulations.

REMAINS OF PRODUCT: Remains of product in the tin should be carefully remove and leave to dry (only in well ventilated places).

ATTENTION: Remains should be harden in small portions far from flammable substances. Much amount of heat is emitting in the time of reaction! Do not spray on naked flame or any incandescent material. Do not smoke.

CLEAN TIN: Tin carefully clean is not harmful waste. code of waste: 08 01 11

TIN PARTLY EMPTY: See remains of product.

14. TRANSPORT INFORMATION

GENERAL INFORMATION: Do not transport with materials class 1 (with the exception of materials class 1.4S) and with some of materials class 4.1 and 5.2. Avoid direct contact with materials class 5.1 and 5.2 in the time of transport. Do not use naked flame and do not smoke. Harmful to aquatic organisms.

ADR/RID: UN 1263 PAINT, 3, III

UN No.	Name of the raw material	Hazard identification number	Warning label required	Classification Code	Packaging group
1263	PAINT	30	3	F1	III

IMDG- Code: PAINT, CLASS 3, UN 1263, PG III, MARRINE POLLUTANT
EmS: F-E, S-E

ICAO/IATA: No data available.

SPECTRAL BASE COAT METALLIC: SB-810 FINE ALUMINIUM, SB-840 FINE SPECIAL ALUMINIUM, SB-820 MEDIUM FINE ALUMINIUM, SB-830 MEDIUM COARSE ALUMINIUM, SB-850 MEDIUM ALUMINIUM, SB-860 BRIGHT COARSE ALUMINIUM, SB-870 EXTRA COARSE ALUMINIUM, SB-880 COARSE ALUMINIUM

Date of issue: 20.07.2006

Date to update: 09.10.2007

Number: SB_8_24_02

Page: 4 of 4

15. REGULATORY INFORMATION

Safety data sheet in accordance with Directives:

67/548/EWG(2006/121/WE)

91/155/EWG (2001/58/WE)

1999/45/EC (2006/8/WE)

2006/1907/WE REACH

Other regulations: ADR (2007-2009) , IMDG Code 2006 Edition

CONTAINS:

Xylene



HAZARD SYMBOL(S)

Xn Harmful

RISK-PHRASES:

R10 Flammable.
R20/21 Harmful by inhalation and in contact with skin.
R66 Repeated exposure may cause skin dryness or cracking.

SAFETY-PHRASES:

S (2-) Keep out of the reach of children.
S 23 Do not breathe vapour/spray.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S 38 In case of insufficient ventilation, wear suitable respiratory equipment
S 43 In case of fire, use powder, foam, sand, CO₂
S 46 If swallowed, seek medical advice immediately and show this container or label

16. OTHER INFORMATION

Full text of the R-Phrases from section 2 and 3:

R10 Flammable

R20/21 Harmful by inhalation and in contact with skin

R22 Harmful if swallowed

R37 Irritating to respiratory system.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

R51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

Carc.cat.2 R45 May cause cancer.

R65 Harmful: may cause lung damage if swallowed.

Information contained herein is based on our current knowledge. This document does not constitute a warranty for product characteristics.

Issued by: NOVOL Sp. z o.o.

Information: Laboratory Research and Development; tel. +48 61 810 99 09