

SAFETY DATA SHEET

Date of issue: 09.07.2007

Date to update: 09.10.2007

Number: SB_8_42

Page: 1 of 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**1.1. Identification of the preparation:** SPECTRAL EXTRA 795 FADE OUT PRODUCT**1.2. Use of the preparation:** For eliminating of optical differences between old and new applied coating.

1.3. Company/undertaking identification: NOVOL Sp. z o.o. Tel: (061) 810-98-00
 ul. Żabikowska 7/9 Fax: (061) 810-98-09
 62-052 Komorniki www.novol.pl
 Emergency tel: (061) 810-98-00

2. HAZARD IDENTIFICATION**HEALTH HAZARDS:** Harmful product. Harmful by inhalation and in contact with skin. Repeated exposure may cause skin dryness or cracking.**DANGEROUS PROPERTIES:** Flammable liquid; that catch fire at temperatures in excess of 21°C if exposed to an ignition source. Avoid contact with strong oxidants.**OTHER:** No data available.**3. COMPOSITION / INFORMATION ON INGREDIENTS**

EEC No.	Name of the substance	WE No.	CAS No.	Classification of the substance	Marking of the substance	Composition
607-025-00-1	Butyl acetate	204-658-1	123-86-4	R10 R66-67	R: 10-66-67 S: (2-)25	30-40%
601-022-00-9	Xylene	215-535-7	1330-20-7	R10 Xn, R20/21 Xi, R38	Xn R: 10-20/21-38 S: (2-)25	<20%
607-130-00-2	Pentyl acetate	211-047-3	628-63-7	R10; R66	R: 10-66 S: (2-)23-24	30-40%
607-038-00-2	2-butoxyethyl acetate	203-933-3	112-07-2	Xn; R20/21	Xn R: 20/21 S: (2-)24	7-10%

4. FIRST AID MEASURES**GENERAL INFORMATION:** See 11 point Product Data Sheet.**INHALATION:** Take the casualty into the fresh air and keep warm irregular breathing/no breathing artificial respiration call a physician.**SKIN:** Take off soiled clothes. Wash off with plenty of lukewarm water with soap (at least 15 minutes).consult a doctor in the event of skin reaction.**EYES:** Hold the eyes open and rinse immediately with plenty of lukewarm water (at least 15 minutes). Contact with ophthalmologist.**ALIMENTARY TRACT:** Do not under any circumstances induce vomiting. SEEK A MEDICAL EXAMINATION IMMEDIATELY and present Safety data sheet. Administer petrolatum; administer neither milk nor animal or vegetable fats of any kind.**5. FIRE-FIGHTING MEASURES****FIRE EXTINGUISHING SUBSTANCES:** Powder, foam, sand, CO₂.**SPECIAL HAZARDS:** Fire may cause the generation of carbon monoxide.**PROTECTIVE EQUIPMENT:** Firemen have to wear self-contained breathing apparatus and protective clothing.**OTHER INFORMATION:** Cool adjacent tanks by spraying water from a safe distance.**6. ACCIDENTAL RELEASE MEASURES****PERSONAL PROTECTION:** Eliminate sources of ignition. Ensure sufficient ventilation in this room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Put on protective equipment see chapter 8.**PROTECTION OF THE ENVIRONMENT:** Prevent to get through to the sewage system, to the surface water, underground water, to the soil. In case of a major spillage the affected area should be separated with bounds.**ACTION IN CASE OF SPILLAGE:** Seal the container; damaged containers should be placed in emergency containers. Besprinkle spillage, use e.g. mica, sand, wood flour. Remove the substance mechanically and put to emergency containers. For further disposal measures: see chapter 13.

SAFETY DATA SHEET
SPECTRAL EXTRA 795 FADE OUT PRODUCT

Date of issue: 09.07.2007

Date to update: 09.10.2007

Number: SB_8_42

Page: 2 of 4

7. HANDLING AND STORAGE

HANDLING RULES: Keep away from heat and sources of fire. Do not smoke. Do not inhale vapours. Avoid contact with skin and eyes. Take precautionary measures against electrostatic loading. Do not eat and drink during working with product. Avoid contact with source of fire, incandescent materials and direct sunshine. Use only in well ventilated place. Put on protective equipment see chapter 8.

STORAGE: Keep in sealed containers in cool, well ventilated rooms. Storage in the vicinity of a large quantity of organic peroxides or strong oxidants is prohibited.

PECULIAR APPLICATION: See the technical product data sheet.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

LIMIT VALUES:

for Xylene CAS 1330-20-7 according to:

- *TRGS 900:* MAK: 100ppm, MAK: 440 mg/m³, 2(II),DFG, H
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 mg/m³, 220mg/m³, STEL 100ppm, 441 mg/m³, Sk, BMGV

for Butyl acetate CAS 123-86-4 according to:

- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 150 ppm, 724 mg/m³, STEL 200ppm, 966 mg/m³

for Pentyl acetate CAS:628-63-7 according to:

- *TRGS 900:* MAK: 50ppm, MAK: 270 mg/m³, 1(I),DFG, EU, H

for 2-butoxyethyl acetate CAS 112-07-2 according to:

- *TRGS 900:* MAK: 20ppm, MAK:130 mg/m³, 4(II) DFG, H, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 20 ppm, STEL 50ppm, Sk

RESPIRATORY TRACT PROTECTION: Gas mask with "A" type absorbing canister.

PROTECTION OF HANDS: Protective gloves (viton, nitrile rubber).

EYES PROTECTION: Protective glasses.

SKIN PROTECTION: Suitable protective clothing (antistatic,impregnated clothing).

WORKPLACE: Topical stays and exhausting ventilation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	liquid
Colour:	colourless
Smell:	characteristic
Boiling point:	126-140°C
Flash-point:	23°C
Autoignition point:	approx.370°C
Explosion limits:	% lower:: 1.0 vol% upper: 8.0 vol% (butyl acetate)
Vapour pressure:	13 hPa (20°C) (butyl acetate)
Density:	---
Water solubility:	poorly soluble
Viscosity Ford φ4:	not applicable

10. STABILITY AND REACTIVITY

STABILITY: The product remains stable under normal conditions.

AVOID THE CONTACT OF THE MATERIAL WITH: Strong oxidants, high temperature, strong acids and basis.

DANGEROUS DECOMPOSITION PRODUCTS: Carbon monoxide and other toxic gasses are generated as a result of thermal decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicological studies at the preparation are not available.

TOXICITY:

Xylene:	LD ₅₀ (rat, oral)	5000 mg/kg
	LC ₅₀ (rat, inhalation)	4550 ppm /4h

IRRITATING EFFECT: Skin: irritating to skin and mucous membranes.
Eyes: irritating effect.

SYMPTOMS OF POISONING: Headache and vertigo, fatigue, decreased muscle power, sleepiness and, in exceptional instances, loss of consciousness. If swallowed, the substance may cause irritation of the alimentary tract, nausea, vomiting, and diarrhoea.

SAFETY DATA SHEET
SPECTRAL EXTRA 795 FADE OUT PRODUCT

Date of issue: 09.07.2007
 Date to update: 09.10.2007

Number: SB_8_42

Page: 3 of 4

12. ECOLOGICAL INFORMATION

Ecological studies at the preparation are not available.

Xylene: Daphnia magna/EC50 (48h.) > 7,4 mg/l
 ID-Number: 206
 Classification under Hazard to Water: 2

Butyl acetate: ID-Number: 42
 Classification under Hazard to Water: 1

The product is very poorly soluble in water. Keep away from the sewage system, surface water, underground water, and soil.

13. DISPOSAL CONSIDERATIONS

RECOMMENDATION: Product must be disposed of by special means in accordance with local regulations.

REMAINS OF PRODUCT: Remains of product in the tin should be carefully remove and leave to dry (only in well ventilated places). code of waste: 14 06 03

ATTENTION: Remains should be harden in small portions far from flammable substances. Dried product is not harmful waste.

TIN PARTLY EMPTY: See remains of product code of waste: 15 01 10

14. TRANSPORT INFORMATION

GENERAL INFORMATION: Do not transport with materials class 1 (with the exception of materials class 1.4S) and with some of materials class 4.1 and 5.2. Avoid direct contact with materials class 5.1 and 5.2 in the time of transport. Do not use naked flame and do not smoke.

ADR/RID: UN 1263 PAINT, 3, III

UN No.	Name of the raw material	Hazard identification number	Warning label required	Classification Code	Packaging group
1263	PAINT RELATED MATERIAL	30	3	F1	III

IMDG- Code: PAINT RELATED MATERIAL,, CLASS 3, UN 1263, PG III, EmS: F-E, S-E

ICAO/IATA: No data available.

15. REGULATORY INFORMATION

Safety data sheet in accordance with Directives:
 91/155/EWG (2001/58/WE)
 67/548/EWG(2006/121/WE)
 1999/45/EC (2006/8/WE)
 2006/1907/WE REACH
 Other regulations: ADR (2005) , IMDG Code 2004 Edition

CONTAINS: Xylene



HAZARD SYMBOL(S) Xn Harmful

RISK-PHRASES: R10 Flammable.
 R20/21 Harmful by inhalation and in contact with skin.
 R66 Repeated exposure may cause skin dryness or cracking.

SAFETY-PHRASES: S (2-) Keep out of the reach of children.
 S 23 Do not breathe vapour/spray.
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
 S 38 In case of insufficient ventilation, wear suitable respiratory equipment
 S 43 In case of fire, use powder, foam, sand, CO₂
 S 46 If swallowed, seek medical advice immediately and show this container or label

SAFETY DATA SHEET
SPECTRAL EXTRA 795 FADE OUT PRODUCT

Date of issue: 09.07.2007

Date to update: 09.10.2007

Number: SB_8_42

Page: 4 of 4

16. OTHER INFORMATION

Full text of the R-Phrases from section 2 and 3:

R10 Flammable

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.

R66 Repeated exposure may cause skin dryness or cracking.

Information contained herein is based on our current knowledge. This document does not constitute a warranty for product characteristics.

Issued by: NOVOL Sp. z o.o.

Information: Laboratory Research and Development; tel. +48 61 810 99 09