

SAFETY DATA SHEET

Date of issue: 20.07.2006

Date to update: 09.10.2007

Number: SB_8_52_01

Page: 1 of 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Identification of the preparation: **SPECTRAL SOLV 875 THINNER FOR BASECOATS STANDARD, SLOW**

1.2. Use of the preparation: The **SPECTRAL SOLV 875 THINNER FOR BASECOATS** is the mixture suitable solvents giving a product with strictly definite parameters assuring its good compatibility with various clearcoats as effect.

1.3. Company/undertaking identification: **NOVOL** Sp. z o.o. Tel: (061) 810-98-00
ul. Żabikowska 7/9 Fax: (061) 810-98-09
62-052 Komorniki www.novol.pl
Emergency tel: (061) 810-98-00

2. HAZARD IDENTIFICATION

HEALTH HAZARDS: Harmful product. Harmful by inhalation and in contact with skin. Irritating to eyes. Harmful; may cause lung damage if swallowed

DANGEROUS PROPERTIES: Highly flammable liquid; avoid contact with strong oxidants. Harmful to aquatic organism, may cause long-term adverse effects in the aquatic environment

OTHER: No data available.

3. COMPOSITION / INFORMATION ON INGREDIENTS

EEC No.	Name of the substance	WE No.	CAS No.	Classification of the substance	Marking of the substance	Composition
607-195-00-7	2-Methoxy-1-methylethyl acetate	203-603-9	108-65-6	R10 Xi; R36	Xi R: 10-36 S: (2-)25	30-70%
607-025-00-1	Butyl acetate	204-658-1	123-86-4	R10 R66-67	R: 10-66-67 S: (2-)25	0-35%
--	Ethyl acetate	205-500-4	141-78-6	F; R11 Xi; R36 R66-67	F; Xi R:11-36-66-67 S: (2-)16-26-33	0-10%
601-022-00-9	Xylene	215-535-7	1330-20-7	R10 Xn, R20/21 Xi, R38	Xn R: 10-20/21-38 S: (2-)25	<10%
607-038-00-2	2-butoxyethyl acetate	203-933-3	112-07-2	Xn, R20/21	Xn R: 20/21 S: (2-)24	<10%
649-356-00-4	Solvent naphtha (petroleum), light arom.	265-199-0	64742-95-6	Xn; R65	Xn, N R: 10-36/37/38-51/53-65-66-67 S:23-24-43a-57-60-62	5-10%
601-043-00-3	1,2,4-trimethylbenzene	202-436-9	95-63-6	R10 Xn; R20 Xi; R36/37/38 N; R51-53	Xn; N R: 10-20-36/37/38-51/53 S: (2-)26-61	1-5%
601-025-00-5	1,3,5-trimethylbenzene	203-604-4	108-67-8	R10 Xi; R37 Xi; N; R37-51/53 N; R51-53	Xi; N R: 10-37-51/53 S: (2-)61	1-2%
601-024-00-X	Cumene	202-704-5	98-82-8	R10 Xn; R65 Xi; R37 N; R51-53	Xn; N R: 10-37-51/53-65 S: (2-)24-37-61-62	0.5-1%

*applied notes H, P and 4; contains weight benzene (no WE 200-753-7) below 0.1% Classification of the substance: no carcinogen

4. FIRST AID MEASURES

GENERAL INFORMATION: See 11 point Product Data Sheet.

INHALATION: Take the casualty into the fresh air and keep warm irregular breathing/no breathing artificial respiration call a physician.

SKIN: Take off soiled clothes. Wash off with plenty of lukewarm water with soap (at least 15 minutes).consult a doctor in the event of skin reaction.

EYES: Hold the eyes open and rinse immediately with plenty of lukewarm water (at least 15 minutes). Contact with ophthalmologist.

ALIMENTARY TRACT: Do not provoke vomiting (risk of choking). Rinse mouth with water. Medical help is required. If vomiting self-righting keep head below hips - Do not allow penetrating to lung.

SAFETY DATA SHEET
SPECTRAL SOLV 875 THINNER FOR BASECOATS STANDARD, SLOW

Date of issue: 20.07.2006

Date to update: 09.10.2007

Number: SB_8_52_01

Page: 2 of 4

5. FIRE-FIGHTING MEASURES

FIRE EXTINGUISHING

SUBSTANCES: Powder, foam resistant to alcohols, carbon dioxide, watermist.

SPECIAL HAZARDS: Fire may cause the generation of carbon monoxide.

PROTECTIVE EQUIPMENT: Firemen have to wear self-contained breathing apparatus and protective clothing.

OTHER INFORMATION: Cool adjacent tanks by spraying water from a safe distance.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION: Eliminate sources of ignition. Ensure sufficient ventilation in this room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Put on protective equipment see chapter 8.

PROTECTION OF THE ENVIRONMENT: Prevent to get through to the sewage system, to the surface water, underground water, to the soil. In case of a major spillage the affected area should be separated with bounds.

ACTION IN CASE OF SPILLAGE: Seal the container; damaged containers should be placed in emergency containers. Besprinkle spillage, use e.g. mica, sand, wood flour. Remove the substance mechanically and put to emergency containers. For further disposal measures: see chapter 13.

7. HANDLING AND STORAGE

HANDLING RULES: Keep away from heat and sources of fire. Do not smoke. Do not inhale vapours. Avoid contact with skin and eyes. Take precautionary measures against electrostatic loading. Use only in well ventilated place. Put on protective equipment-see chapter 8.

STORAGE: Keep in sealed containers in cool, well ventilated rooms. Storage in the vicinity of a large quantity of organic peroxides or strong oxidants is prohibited.

PECULIAR APPLICATION: See the technical product data sheet..

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

LIMIT VALUES:

for Xylene CAS 1330-20-7 according to:

- *TRGS 900:* MAK: 100ppm, MAK: 440 mg/m³, 2(II),DFG, H
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 mg/m³, 220mg/m³, STEL 100ppm, 441 mg/m³, Sk, BMGV

for 2-methoxy-1-methylethyl acetate CAS 108-65-6 according to:

- *TRGS 900:* MAK: 50ppm, MAK: 270 mg/m³, 1(I),DFG, EU, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 ppm, 274 mg/m³, STEL 100ppm, 548 mg/m³, Sk

for Butyl acetate CAS 123-86-4 according to:

- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 150 ppm, 724 mg/m³, STEL 200ppm, 966 mg/m³

for Ethyl acetate CAS 141-78-6 according to:

- *TRGS 900:* MAK: 400ppm, MAK: 1500 mg/m³, 2(I),DFG, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 200 ppm, STEL 400ppm

for 2-butoxyethyl acetate CAS: 112-07-2 according to:

- *TRGS 900:* MAK: 20ppm, MAK: 130 mg/m³, 4(II),DFG, H, Y

for 1,2,4-trimethylbenzene CAS 95-63-6 according to:

- *TRGS 900:* MAK: 20ppm, MAK: 100 mg/m³, 2(II),DFG,EU, Y

for 1,3,5-trimethylbenzene CAS 108-67-8 according to:

- *TRGS 900:* MAK: 20ppm, MAK: 100 mg/m³, 2(II),DFG,EU, Y

for Cumene CAS 98-82-8 according to:

- *TRGS 900:* MAK: 20ppm, MAK: 100 mg/m³, 2,5(I),EU,H, Y

RESPIRATORY TRACT PROTECTION: Gas mask with "A" type absorbing canister.

PROTECTION OF HANDS: Protective gloves suitable for handling solvents (viton, nitrile rubber, vinyl □olyalcohol).

EYES PROTECTION: Protective glasses.

SKIN PROTECTION: Suitable protective clothing (antistatic, impregnated clothing).

WORKPLACE: Topical stays and exhausting ventilation.

SAFETY DATA SHEET**SPECTRAL SOLV 875 THINNER FOR BASECOATS STANDARD, SLOW**

Date of issue: 20.07.2006

Date to update: 09.10.2007

Number: SB_8_52_01

Page: 3 of 4

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	liquid
Colour:	colourless
Smell:	pungent, penetrating odour
Boiling point:	126-140°C
Flash-point:	23°C
Autoignition point:	>270°C
Explosion limits:	---
Vapour pressure:	---
Density:	approx. 0.95 g/cm ³ (20°C)
Water solubility:	poorly soluble
Partition coefficient n-octanol/water:	--
Viscosity (rotating rheometer):	approx. 1mPas

10. STABILITY AND REACTIVITY

STABILITY:	The product remains stable under normal conditions.
AVOID THE CONTACT OF THE MATERIAL WITH:	Strong oxidants, high temperature, strong acids and basis.
DANGEROUS DECOMPOSITION PRODUCTS:	Carbon monoxide and other toxic gasses are generated as a result of thermal decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicological studies at the preparation are not available.

TOXICITY: Xylene:	LD ₅₀ (rat, oral)	5000 mg/kg
	LC ₅₀ (rat, inhalation)	4550 ppm/4h
Butyl acetate:	LD ₅₀ (rat, oral)	14000 mg/kg
	LC ₅₀ (rat, inhalation)	9660 mg/m ³ /8h

IRRITATING EFFECT: Skin: irritating to skin and mucous membranes.
Eyes: irritating effect.

SYMPTOMS OF POISONING: Headache and vertigo, fatigue, decreased muscle power, sleepiness and, in exceptional instances, loss of consciousness. If swallowed, the substance may cause irritation of the alimentary tract, nausea, vomiting, and diarrhoea.

12. ECOLOGICAL INFORMATION

Ecological studies at the preparation are not available.

2-Methoxy-1-methylethyl acetate:	Daphnia magna/EC50 (48h.) > 500 mg/l Oncorhynchus mykiss/LC50 (96h.) 100-180 mg/l Number in catalogue includes substance danger to water : 5033 Water hazard class : 1
Xylene:	Daphnia magna/EC50 (48h.) > 7,4 mg/l ID-Number: 206 Classification under Hazard to Water: 2
Butyl acetate:	ID-Number: 42 Classification under Hazard to Water: 1

The product is very poorly soluble in water. Keep away from the sewage system, surface water, underground water, and soil. Harmful to aquatic organism, may cause long-term adverse effects in the aquatic environment

13. DISPOSAL CONSIDERATIONS

RECOMMENDATION:	Product must be disposed of by special means in accordance with local regulations.
REMAINS OF PRODUCT:	Remains of product in the tin should be carefully remove and leave to dry (only in well ventilated places).
ATTENTION:	Remains should be dry in small portions far from flammable substances. Do not dry close to naked flame or any incandescent materials. Do not smoke.
CLEAN TIN:	Tin carefully clean is not harmful waste. code of waste: 14 06 03
TIN PARTLY EMPTY:	See remains of product.

SAFETY DATA SHEET**SPECTRAL SOLV 875 THINNER FOR BASECOATS STANDARD, SLOW**

Date of issue: 20.07.2006

Date to update: 09.10.2007 Number: SB_8_52_01 Page: 4 of 4

14. TRANSPORT INFORMATION**GENERAL INFORMATION:**

Do not transport with materials class 1 (with the exception of materials class 1.4S) and with some of materials class 4.1 and 5.2. Avoid direct contact with materials class 5.1 and 5.2 in the time of transport. Do not use naked flame and do not smoke.

ADR/RID:

UN 1263 PAINT RELATED MATERIAL 3, III.

UN No.	Name of the raw material	Hazard identification number	Warning label required	Classification Code	Packaging group
1263	PAINT RELATED MATERIAL	30	3	F1	III

IMDG- Code:

PAINT RELATED MATERIAL, CLASS 3, UN 1263, PG III.
EmS: F-E, S-E

ICAO/IATA:

No data available.

15. REGULATORY INFORMATION

Safety data sheet in accordance with Directives:

67/548/EWG(2006/121/WE)

91/155/EWG (2001/58/WE)

1999/45/EC (2006/8/WE)

2006/1907/WE REACH

Other regulations: ADR (2007-2009) , IMDG Code 2006 Edition

CONTAINS:

Xylene

**HAZARD SYMBOL(S)**

Xn Harmful

RISK-PHRASES:

R10 Flammable.
R20/21 Harmful by inhalation and in contact with skin.
R36 Irritating to eyes
R 65 Harmful; may cause lung damage if swallowed
R52/53 Harmful to aquatic organism, may cause long-term adverse effects in the aquatic environment

SAFETY-PHRASES:

S (2-) Keep out of the reach of children.
S 23 Do not breathe vapour/spray.
S 29 Do not empty into drains
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S 38 In case of insufficient ventilation, wear suitable respiratory equipment
S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

16. OTHER INFORMATION

Full text of the R Phrases from section 2 and 3:

R10 Flammable

R20/21 Harmful by inhalation and in contact with skin

R36 Irritating to eyes

R37 Irritating to respiratory system.

R38 Irritating to skin.

R51/53 Toxic to aquatic organism, may cause long-term adverse effects in the aquatic environment

R52/53 Harmful to aquatic organism, may cause long-term adverse effects in the aquatic environment

R 66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Information contained herein is based on our current knowledge. This document does not constitute a warranty for product characteristics.

Issued by: NOVOL Sp. z o.o.

Information: Laboratory Research and Development; tel. +48 61 810 99 09