

## ELASTICITY INCREASING AGENT - SPECTRAL PLAST 775

**Characteristics:**

**ELASTICITY INCREASING AGENT Spectral PLAST 775** – is a plasticizer for acrylic and polyurethane products designed mainly for application onto car body parts made of plastics. It prevents cracking and chipping of the fillers and topcoats on elastic, deforming elements. It may be used to elasticise of topcoats on elements exposed to damage by stones (e.g. front part, bonnet).

**Apply with:**

- Acrylic primer SPECTRAL UNDER 335
- Acrylic primer SPECTRAL UNDER 355
- Acrylic clearcoat SPECTRAL UNDER 515
- Acrylic clearcoat SPECTRAL UNDER 575
- Coloured topcoats SPECTRAL 2K series

**Mixing ratio:**

Depending on the elasticity of the surface the agent can be used in amount of 10 ÷ 30 % by volume. It should be counted on a ready mixture of the product with the hardener, properly correcting the amount of the thinner. It does not affect neither the potlife of the ready mixture nor the adjustment of the spray gun.

**Colour:**

Colourless.

**Storage time and condition:**

Store in a dry, cool place, away from sources of fire and heat. Direct sunlight should be avoided.  
24 months at a temperature of 20°C.

**Industrial safety:**

See Safety Data Sheet of this article.

Effectiveness of our systems is the result of laboratory testing and many years of experience. We guarantee high quality of our products provided all relevant instructions and guidelines are strictly adhered to and work performed is consistent with good industrial practice. We shall not be held responsible for any deficiencies due to circumstances beyond our control.

NOVOL Ltd., Komorniki, Poland