

## SPECTRAL EXTRA 795 – Fade Out Agent

**Characteristics:**

**SPECTRAL EXTRA 795** – Fade out Agent, is designed for eliminating of optical differences between old paint coating and the new layer of base coat.

**Application:**

Use at applying:

- SPECTRAL BASE base coats

**Spray viscosity, nozzle, pressure:**

Product is supplied in ready-to-use form.

DIN 4/20°C, approx. 10 s,

HVLP – 2 bar, Ø1.3÷1.4mm nozzle

HP - 3÷4 bar, Ø1.3÷1.4mm nozzle

**Procedure:**

SPECTRAL EXTRA 795 – Fade out Agent should be applied in one thin coat in place where the new layer of base coat overlaps the old paint coating. After 5-10 minutes the SPECTRAL EXTRA 795 – Fade out Agent was applied, SPECTRAL BASE coat can be used.

**Colour:**

Colourless.

**Storage time and condition:**

Store in a dry, cool place, away from sources of fire and heat. Direct sunlight should be avoided. 24 months at a temperature of 20°C.

**Industrial safety:**

See Safety Data Sheet of this article.

Effectiveness of our systems results from lab research and many years long experience. We guarantee high quality provided that our recommendations are observed and the works are performed according to the good craftsmanship practice. We may not be held liable for defects if the final results are affected by factors beyond our control.

NOVOL Ltd. Komorniki, PL