

Acryl Thinner - SPECTRAL SOLV 855

Characteristics:

Acryl Thinner SPECTRAL SOLV 855 is a mixture of solvents giving a product applied for thinning all fillers and acrylic lacquers. It occurs in three version: Fast, Normal and Slow, which allow to use appropriate thinner depending on temperature of work and size of repair.

Procedure:SPECTRAL SOLV 855 Fast Thinner:

It is usually applied for small repairs. It can be also used in case of painting larger surfaces but in temperature not exceeding 20°C.

SPECTRAL SOLV 855 Normal Thinner:

It is applied in case of painting large surfaces in the range of 20 - 25°C.

SPECTRAL SOLV 855 Slow Thinner:

It is applied in case of painting large surfaces in the range 25 - 35°C.

Can be used with:

- Spectral 2K Topcoat,
- Spectral UNDER 355 acrylic primer,
- Spectral UNDER 335 acrylic primer

Mixing ratio:

Ratios given in technical data sheet of individual product should be used.

Colour:


Colourless.

Storage time and condition:

Store in a dry, cool place, away from sources of fire and heat. Direct sunlight should be avoided.
24 months at a temperature of 20°C.

Industrial safety:

See Safety Data Sheet of this article.



Technical Data Sheet Acryl Products.

Effectiveness of our systems is the result of laboratory testing and many years of experience. We guarantee high quality of our products provided all relevant instructions and guidelines are strictly adhered to and work performed is consistent with good industrial practice. We shall not be held responsible for any deficiencies due to circumstances beyond our control.

NOVOL Ltd., Komorniki, Poland