

Strong IMPREGNATE

Description:

The product is designed for impregnation of natural stone, terracotta, terrazzo, concrete, pitcher, etc. It can be applied on both indoor and outdoor details. The impregnate protects the surface from liquids and fats. It does not leave a sealed film, which enables breathability. The product improves scratching resistance. It does not affect the substrate colour.

Technical data:	Strong impregnate
Density	1.0 g/cm ³
Appearance	Colourless liquid
Drying time	Ca. 30 min at 20°C
Full impregnation	24 hours
Form	Aqueous, solvent-free and ready to use product.

Surface preparation:

Ensure that the stone surface is clean and degreased before application. The product can be applied on damp surfaces; however, the substrate cannot be excessively wet. Impregnate after all other works.

Capacity:

Ca. 100g/m² – low absorption materials;
Twice per ca. 100g/m² – absorptive materials.

Procedure:

Apply a uniform layer of the product with a roller, a brush or by spraying. Avoid puddles. Inspect the stone surface during application to evaluate the absorptivity. Stone is a natural material; hence it is recommended to test the effect of impregnation on a hidden place to assess the absorptivity of the stone and the final result. Do not apply the impregnate on resin or non-absorbing surfaces. If the substrate is highly absorbing, apply the second layer after ca. 30 minutes from the first one.


CAUTION: Shake the container well before each use until any white deposits are completely dissolved.



Clean
the surface



Shake



Apply
100g/m²



24 hours

Equipment cleaning:

Running water.

Storage conditions and shelf life:

Store in factory-sealed containers between +5 and +40°C.
12 months at 20°C.

Safety regulations:

See the Safety Data Sheet of the product in question.

Packaging:

Available in 0.2 l, 1 l and 5 l containers.