

CARE AGENT SUPRACLEAN 400 SEMI MAT

Description:

SUPRACLEAN 400 Semi Mat is a water-based wood care and maintenance product for wooden parquets and floors. Thanks to a special polymer resin, the product coats the floor with a durable film and protects it against abrasion, scratches and contamination.

Use:

The product is intended for protecting varnish-coated parquets and floorboards. It can be applied on floors exposed to low or high intensity of use, such as public utility objects.

SUPRACLEAN 400 wood care product is recommended for half mat varnishes, as it intensifies the shine. Do not apply to waxed or polished floors.

Procedure:

Prior to application, ensure that the surface is clean, dry and degreased. The surface can be prepared using the Supraclean 200 or Supraclean 100 Cleaning Agent.

Apply the wood care product using a flat microfibre mop or a soft cloth. When applying, make sure to distribute a thin layer of the product evenly. Left out spots may only be coated after the product has dried on the surface. Coating the left-out spaces during product application may compromise the aesthetic properties by leaving streaks.

The floor can be used after 60 minutes from the application. Use non-diluted.

Fresh layers of varnish must be at least 3-weeks old to be protected with the wood care product.

If abrasions occur during use, a new layer of product may be applied. Repeat this procedure:

1-2 times a year, for rooms exposed to low intensity of use – apartments

3-4 times a year, for rooms exposed to high intensity of use – public utility objects

After applying 4 layers, remove the care product film using the Supraclean 100 remover of protective coatings.

Application conditions:

Room temperature should range between 10° and 25°C.

Drying time:

Approx. 30 minutes, at room temperature (20°C) and air humidity of approx. 50 - 70%

Colour:

- In packaging: milk-white

- After application: colourless, slight shine intensifying effect.

Scent:

Gentle, hardly noticeable

Capacity:

12-17 ml/m² (1litre for 60-80 m²)

Application methods:

Flat mop, soft cloth.

Tools cleaning:

Clean with water directly after use.

Storage conditions and shelf life:

12 months from date of manufacture at a temperature higher than 5°C.

Packaging:

Canister 1 l.